

Product: Wall Paper "Adhesivo Reposicionable" Mural

General Description:

Polyester self-adhesive sticky fabric for Wider Format Inkjet Printing
¡á Suitable for unique applications such as wall covering, shop-window decoration, exhibition booth and interior display etc.

Based Material:

100% woven polyester white dyed.

WP : 100% polyester D.T.Y 150D

WT : 100% polyester D.T.Y 150D

Yarn Weight : 110 g/§³

Coating Components:

Milky-white liquid, Solution involving Polyurethane.

Coating Weight : 90 g/§³

Self Adhesive:

Permanent glue backing.

Adhesive Film : PET 50 mic.

Backing Weight : 70 g/§³

Coating Method:

Printing surface : Knife Coating Method

Backing Glue : Commma Coating method

Technical Sheet:

Denier	warp	150	Surface	Matt
	wert	150	FR treatment	FR
Thickness		0.24 mm		
Weight		270 g/m²	Backing Adhesive Film	PET
Fabric Count (pick/2.54cm)	warp	80		50 mic.
	wert	61.2		70 g/m²
Breaking Strength*	warp	793.4	Width (mm)	
	wert	583.7		
Tearing Strength*	warp	18.76		1524
	wert	14.7		
Colorfastness to light 20 Hrs.*		Grade : 3~4	Compitable Ink	Solvent
				Eco-Solvent
			Core	UV Curable
				3"

* Breaking Strength : Grab Method (10x15cm) [kgf]=0.102x[N]

* Tearing Strength : Pendulum Method [kgf]=0.102x[N]

* Colorfastness to Light 20 hrs. : Xenon arc lamp weather-0-meter : Blue scale

EMASER

Polígono Industrial La Baileta " Can Xinxà"
Calle A, nº9 - 08348 Cabrils (BCN) - Spain
Telf.: +34 750 99 00 - Fax: +34 93 750 99 09
emaser@emaser.com