

Description

This double-sided tape consists of a polypropylene film carrier, layered on both sides with a rubber adhesive. The aging resistant adhesive is lined with a double-sided silicone paper.

Carrier

Polypropylene film, 28 micron

Liner

Silicone coated paper on both sides, 80 g/m², brown

Adhesive

Rubber

Area of use

This tape is a standard tape for the adhesion of a variety of materials. Its high flexibility makes it suitable as an assembly aid. Limited consistency in the presence of chemicals inclined to migrate (plasticisers). Not appropriate for artificial stone floors or marble.

Technical data

Thickness* (adhesive + carrier)	110 micron	
Temperature resistance***	-20°C to +70 °C	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	17 N/25mm
	after 20 min	18 N/25mm
	after 24 h	20 N/25mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	72 h	at 23°C
	5 min	at 70°C
Shelf life**	1 year	
Application temperature	> +15°C	

* average ** in original packaging, at 20°C and 50% relative humidity

*** 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.