

Data sheets

creasefree heavy satin FR + w

Article number: 4102 / 26
Material: 100 % PES
Weight: ca. 280 g/m²

Specialities:

crease resistant
not elastic
not transparent for frame systems
heat set for Sublimation

Applications:

soft signage / Pop up display systems
table cloth
banners
display frame systems

Remarks:

both sides printable: one side satin, other side matte

Product compatibilities:

creasefree heavy satin FR + w is compatible to the following printers (print-method):

| | |
|---|--------------------------------------|
| Vutek FabriVu (Sub Oil) | D-Gen Teleios (Sub water) |
| Gandi Jeti 3312 DS (Sub Oil) | Vutek QS Series (UV curable) |
| Durst Rho 160/350/500 (UV curable) | Dupont Artistri (Sub water) |
| Mimaki JV 4 / TX2 sub direct (Sub water) | HP Expedio 3200 / 5000 (UV curable) |
| Paper Transfer (Sub Paper) | Spühl Virtu (UV curable) |
| Gandi Aquajet (sub water) | ATP Color/Roland (Sub water) |
| Hollanders Colorbooster (Sub water) | Mimaki DS series (Sub water) |
| Mutoh Viper (Sub water) | Roland FP 740 (Sub water) |

Product attributes:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.