

## Data sheets

### eco Display 210 FR + w

Article number: 4280/26eco  
Material: 100 % PES  
Weight: ca. 210 g/m<sup>2</sup>

Kuhleshütte 84  
47809 Krefeld  
Germany

Phone: +49 (0)2151 65231-0  
Fax: +49 (0)2151 65231-25  
Email: info@bergertextil.com  
Internet: www.bergertextil.com

#### Specialities:

crease resistant  
elastic ca. 2-3%  
not transparent for frame systems  
heat set for Sublimation  
no fraying

#### Applications:

soft signage / Pop up display systems  
X-Kite Display Systems  
banners  
roll up display systems  
display frame systems

#### Remarks:

Stretch: ca. 1-2 % length direction, ca. 2-3 % width and diagonal direction

the perfect all round textile for dyesub direct printers like Aquajet (Gandi), Artistri (Dupont), Teleios (Dgen), etc.

\* special size for HP Latex printers

#### Product compatibilities:

eco Display 210 FR + w is compatible to the following printers (print-method):

Vutek FabriVu ( Sub Oil)	D-Gen Teleios ( Sub water)
Gandi Jeti 3312 DS ( Sub Oil)	Vutek QS Series ( UV curable)
Durst Rho 160/350/500 ( UV curable)	Dupont Artistri ( Sub water )
Mimaki JV 4 / TX2 sub direct ( Sub water)	HP Expedio 3200 / 5000 ( UV curable)
Paper Transfer ( Sub Paper )	Spühl Virtu ( UV curable)
Gandi Aquajet ( sub water)	ATP Color/Roland ( Sub water)
Hollanders Colorbooster ( Sub water)	Mimaki DS series ( Sub water)
Mutoh Viper ( Sub water)	Roland FP 740 ( Sub water)
HP Designjet Latex 65500 ( Latex)	

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.

**Product attributes:**