

Data sheets

fineart canvas Rubens

Article number: 4235 / 60
Material: cotton / PES
Weight: ca. 300 g/m²

Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Specialities:

creaseing
not transparent for frame systems
white creasing possible
no fraying
good flatness
dimension stable

Applications:

banners
art reproduction
Textile wallpaper

Remarks:

topseller for art reproductions printed with UV curable or solvent inks.

Master rolls for converters available

*special size for HP Latex printers

Product compatibilities:

fineart canvas Rubens is compatible to the following printers (print-method):

| | |
|--------------------------------------|--|
| Vutek UltraVu 33xx / 53xx (Solvent) | HP Scitex Pressjet (Solvent) |
| Vutek QS Series (UV curable) | NUR salsa ultima (Solvent) |
| Durst Rho 160/350/500 (UV curable) | NUR Fresco HIQ (Solvent) |
| HP Expedio 3200 / 5000 (UV curable) | HP-Scitex XL Jet 2 / 3 / 5 (Solvent) |
| Océ Arizona (Solvent) | Mimaki JV 3 (eco solvent) |
| HP 10000s series (eco solvent) | Spühl Virtu (UV curable) |
| Keundo Supra Series (Solvent) | Mutoh Spitfire/Valuejet (eco solvent) |
| Roland Soljet Series (eco solvent) | HP Designjet Latex 65500 (Latex) |

Product attributes:



++ 49 2151 65231-0



Data sheets

fineart canvas Rubens



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0

Fax: +49 (0)2151 65231-25

Email: info@bergertextil.com

Internet: www.bergertextil.com

Product image:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.