

Data sheets

PES tafetta 55 FR + w

Article number: 4001 / 6
Material: 100 % PES
Weight: 55 g/m²

Specialities:

crease resistant
transparent
very good print through
heat set for Sublimation

Applications:

flags
banners
back projections

Product compatibilities:

PES tafetta 55 FR + w is compatible to the following printers (print-method):

Mimaki JV5 320S / -DS (Sub water)	Agfa/Gandi Aquajet (sub water)
D-Gen Teleios (Sub water)	Paper Transfer (Sub Paper)
Vutek FabriVu (Sub Oil)	

Product attributes:



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Data sheets

PES tafetta 55 FR + w

Testscores:

MATERIAL SAFETY DATASHEET:

100% PES/Polyester

plus additive Flame retardant

HAZARDS IDENTIFICATION:

According to the present state of knowledge there is no known danger to humans

The product is not suitable for human consumption

FIRST AID MEASURES:

After contact with skin or eyes: rinse with lots of water

DISPOSAL:

The product can be disposed with the household waste or can be recycled

FURTHER INFORMATION/CERTIFICATES:

Please request at www.bergertextil.com



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.

Data sheets


PES tafetta 55 FR + w



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Product image:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.