

Data sheets

Solvo flag 100 FR + wS

Article number: 3745 / 73
Material: 100 % PES
Weight: ca. 95 g/m²

Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Specialities:

tearproof
transparent
heat set for Sublimation
no fraying

Applications:

banners
flags
Beach Flags

Remarks:

New: recommended by Vutek for Fusion solvent DyeSub.
Recommendd for front view Application ,because of not perfect print through

Product compatibilities:

Solvo flag 100 FR + wS is compabbtile to the following printers (print-method):

Vutek FabriVu (Sub Oil)	D-Gen Teleios (Sub water)
Gandi Jeti 3312 DS (Sub Oil)	Vutek UltraVu 33xx / 53xx (Solvent)
HP Scitex Pressjet (Solvent)	Vutek QS Series (UV curable)
NUR salsa ultima (Solvent)	Durst Rho 160/350/500 (UV curable)
NUR Fresco HIQ (Solvent)	Dupont Artistri (Sub water)
Mimaki JV 4 / TX2 sub direct (Sub water)	HP Expedio 3200 / 5000 (UV curable)
HP-Scitex XL Jet 2 / 3 / 5 (Solvent)	Océ Arizona (Solvent)
Mimaki JV 3 (eco solvent)	Paper Transfer (Sub Paper)
HP 10000s series (eco solvent)	Spühl Virtu (UV curable)
Gandi Aquajet (sub water)	Vutek 3360 Fusion (Sub sol)
ATP Color/Roland (Sub water)	Hollanders Colorbooster (Sub water)
Mimaki DS series (Sub water)	Mutoh Viper (Sub water)
Roland FP 740 (Sub water)	Keundo Supra Series (Solvent)
Mutoh Spitfire/Valuejet (eco solvent)	Roland Soljet Series (eco solvent)

www.bergertextil.com

Product attributes:

++ 49 2151 65231-0

The information in this information sheet is based on findings obtained in practice. Because of the high number of factors which can have an effect on the handling and application, our customer's tests will be required to fully benefit from the specific properties of the product. The information given here may be subject to change without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.



Data sheets


Solvo flag 100 FR + wS



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Product image:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.