

Data sheets

Stretch canvas 240 FR +w

Article number: 4299-26
Material: 100 % PES
Weight: 260 g/m²

Specialities:

crease resistant
elastic ca. 2-3%
not transparent for frame systems

Applications:

Display frame systems
Display Pop up systems
theatre backdrops

Remarks:

very good crease recovery
front side fine structure
back side canvas structure

Product compatibilities:

Stretch canvas 240 FR +w is compatible to the following printers (print-method):

HP Latex LX 800/ 820/ 850 (Latex)	Durst Rhotex 320 (Sub water)
Mimaki JV5 320S / -DS (Sub water)	Mutoh Viper TX series (Sub water)
D-Gen Teleios (Sub water)	Paper Transfer (Sub Paper)
Vutek 3360 Fusion (Sub sol)	HP Expedio 3200 / 5000 (UV curable)
Durst Rho UV series (UV curable)	Vutek UltraVu 33xx / 53xx (Solvent)

Product attributes:



Data sheets


Stretch canvas 240 FR +w



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Product image:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.