



ANTI-SLIP TAPE - TECHNICAL DATA

TECHNICAL DESCRIPTION	UNIT OF MEASUREMENT	TECHNICAL VALUE
Carrier	Micron	PVC Film 100 micron
Adhesive		Solvent Acrylic
Anti Slip Material	Grit	36 Grit Aluminium Oxide
Liner	Grams	100 g.s.m. PE Paper
Adhesion	Grams/25mm	1500
Tensile Strength	Grams/25mm ²	6000
Elongation at Break		25%
Temperature Range	°C	-30 ⁰ / +60°C
Water Resistance		Good
U.V Resistance		Good

ANTI-SLIP TAPES

Application instructions

- The Surface to which the anti-slip tape is to be applied needs to be clean, dry and free from dust and grease. **(A)**
- Certain floors may need to be degreased (kitchens, and oily industrial floors).
- The best results will be achieved if the surface to which the tape is to be applied is relatively smooth.
- The protective paper liner should be removed from the adhesive surface, then the tape should be applied in alignment, smoothly and evenly. **(B)**
- To gain the best results, pressure should be applied along the full surface area of the tape, ideally with a roller. **(C)**
- Certain surfaces that are porous, such as untreated wood and concrete, may have to be sealed prior to applying the tape.

