

ImagePerfect™ 2921 is a matt, grey-back print medium with good blackout properties for POS and roll-up display systems. This product has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as latex and UV-cured inks.

IP 2921

ImagePerfect™ 2921 is a good quality material (PP) for a wide range of display and roll-up applications. It has good layflat properties and high levels of opacity. As well as increasing the opacity, the grey back-side also adds aesthetic value to the product in relation to a more standard roll-up product. Important recommendation: To protect the printed surface from abrasion, dirt or humidity, we would recommend using a filmic overlamine. The printed IP 2921 must be completely dry prior to application of the laminate. Laminate: IP 2830-202.

Specifications	
DESCRIPTION	Roll-up media, grey-back
COLOUR	White satin
THICKNESS	170μ
WEIGHT	175g/m ²
TEMPERATURE RANGE	-10°C to +55°C
DURABILITY (UNPRINTED)	N/A
FLAME RETARDANCY	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© September 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.