

ImagePerfect™ 2558

White MultiGrip Vinyl (FR)

ImagePerfect™ 2558 MultiGrip is a white semi-gloss vinyl that has been specifically engineered to adhere to challenging surfaces, including brick, concrete, stone and LSE (low surface energy) substrates, on which more conventional adhesive systems will not bond. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfect™ 2558 MultiGrip has been specifically engineered to adhere to challenging flat and textured substrates on which more conventional adhesive systems will find it difficult to bond. This will include brick walls, concrete walls, stone walls, stucco tiling, construction machinery and equipment with a hammertone finish, as well as LSE (low surface energy) substrates such as hard plastics, polyamide (for instance, in ice hockey stadiums), water-based car paints, surf boards, motocross bikes, quad bikes, powder-coated metal substrates, etc. Typical applications will take place at no less than 5°C (otherwise any moisture present will potentially inhibit the adhesive bond), but IP 2558 also performs well in cold temperature environments and can be applied at temperatures as low as 0°C. In such cases, additional process security for the applied graphics can be achieved by the appropriate post heating (to warm the product). IP 2558 promotes high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area infills. It is equipped with a backing paper that offers excellent lay flat properties. Laminate: IP 2810-101, IP 2810-200 or IP 2810-300 for flat surfaces but no lamination necessary (or available) for textured surfaces such as brick.

Attention: Please make sure the printed IP 2558 is completely dry before laminating and/or application. If the printed IP 2558 is not completely dry before laminating, it can negatively affect the adhesive performance. If the printed IP 2558 is not completely dry before application, it can show very high shrinkage and edge curling. Before the IP 2558 is applied, the surface should be completely cleaned so that it is free of dust, dirt and other debris. On "hard to stick to" surfaces, we would recommend a test to confirm that the product will bond before full application takes place. Applications onto structured surfaces will require heat (until the film is soft).

Specifications	
Description	Polymeric vinyl
Colour	White semi-gloss
Thickness	90mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	32N/25mm (Finat TM 1/24h) (16N/25mm on LSE)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +120°C
Application Temperature	Minimum of 0°C but will require additional heat; otherwise, no less than 5°C
Durability (unprinted)	7 years
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.s.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.