

## ImagePerfect<sup>™</sup> 2593 Clear Window Film (FR)

ImagePerfect<sup>™</sup> 2593 Clear Window Film is a highly transparent clear film that is especially engineered for applications on windows, glass panels and mirrors. This product has been created for digital printing on large-format inkjets and is suitable for printing with eco-solvent and solvent inks, as well as UV-cured and latex inks.

ImagePerfect<sup>TM</sup> 2593 Clear Window Film is a highly transparent print media that is supported on a polyester liner (which further enhances the transparency of the film in application). It provides high levels of print quality with a large colour gamut that ensures colourful images with vibrant area in-fills. Unprinted areas of the product offer high levels of clarity through the material; significantly better than those of standard clear printable products. This means that complex shapes do not need to be contour cut. It is ideal for both decorative and functional applications on glass, including interior design applications, branding and advertising opportunities, POS/POP promotional advertising, for information placement and for enhanced privacy screening. As such, it can be used on windows in offices, seminar rooms, trade shows, shops, shopping malls, dividing walls, vehicles, and in many lifestyle and event business locations, such as bars, restaurants, hotels, casinos, cinemas, theatres, sports arenas, etc. It can also be used for many other applications, such as decorative and informative displays on mirrors and it can also be used in combination with a product such as IP 2594 Blockout Vinyl Polymeric for double-sided graphics with no showthrough from one side to the other. IP 2593 is suitable for both indoor and outdoor applications but it is not recommended for windows with built-in heating elements or coatings. The removal of some installations will be facilitated with heat. Wet application is recommended. Laminate: IP 2593. Please note that if IP 2593 is overlaminated, it will lose some of its transparency.

Attention: Please ensure that the printed IP 2593 is completely dry before laminating. Before the IP 2593 is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match-component cleaning solution to ensure that the surface is dry and free of dust and grease. For wet application, please use IP Magic Apply (MIPMAGICAPPLY1).

Specifications	
Description	Polymeric vinyl
Colour	Clear gloss
Thickness	80mym
Weight	N/A
Adhesive	Solvent based acrylic, semi-permanent
Adhesive Strength	10N/25mm (Finat TM 1/24h)
Release Paper	Frosted polyester, 75mym
Temperature Range	-30°C to +80°C
Durability (unprinted)	5 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom