

ImagePerfect[™] 2840-106 Clear Gloss Anti-Graffiti Laminate (FR)

ImagePerfect™ 2840-106 is a polyester laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting digital prints from graffiti.

ImagePerfectTM 2840-106 is an environmentally-friendly, plasticiser-free laminate that offers resistance to a wide variety of chemicals, solvents and staining agents. As such, it is ideal for the lamination of markings and decorations, protecting them from any permanent damage that would otherwise result from exposure to graffiti, including spray paints, felt-tip marker pens and other staining agents. In conjunction with IP 2840-106, graffiti can be easily removed with the help of common solvents or proprietary cleaning products such as IP Surface Cleaner and/or IP Magic Clean. As a 100% PET product, it will also present a "greener" laminate solution for end-users who are looking to add environmentally-friendly credibility to their output than would otherwise be presented with more standard PVC laminate options. It is also a very effective solution for paper lamination specifically, providing protection for photographic and graphic prints, including commercial poster prints. It is supported on a clear polyester release liner that provides complete visual inspection of the product, easy liner removal and a distortion-free adhesive surface with high levels of clarity in application. Please note that IP 2840-106 is not suitable for application to apolar, low-energy surfaces (including PE and PP) and it should only be used on flat surfaces. IMPORTANT: This special laminate is impervious to gas and moisture and it is essential that the print media is completely dry prior to application of this laminate.

Specifications	
Description	PET laminate
Colour	Clear gloss
Thickness	25mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	13N/25mm (Finat TM 1/24h)
Release Paper	Siliconised polyester, 30mym
Temperature Range	-20°C to +140°C
Durability (unprinted)	4 years
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity

[©] May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom